In the Claims

- 1. (cancelled)
- 2. (currently amended) A sailing boat according to claim [[1]] 41, wherein said hull is a single hull.
- 3. (currently amended) A sailing boat according to claim [[1]] 41, wherein said loop is elliptical.
- 4. (currently amended) A sailing boat according to claim [[1]] 41, wherein said loop is ovoid, with an apex at the top of the mast.
- 5. (currently amended) A sailing boat according to claim [[1]] 41, wherein the maximum beam of said mast is in the range 60 to 90 percent of its height.
- 6. (original) A sailing boat according to claim 5, wherein the maximum beam of said mast is in the range 65 to 85 percent of its height.
- 7. (original) A sailing boat according to claim 6, wherein the maximum beam of said mast is in the range 70 to 80 percent of its height.
- 8. (original) A sailing boat according to claim 7, wherein the maximum beam of said mast is substantially 75 percent of its height.
- 9. (currently amended) A sailing boat according to claim[[1]] 41, wherein said mast is formed of at least one closed hollow member.
- 10. (original) A sailing boat according to claim 9, wherein said mast is formed of a single closed hollow member having ends that are connected at the top of the mast.
- 11. (original) A sailing boat according to claim 9, wherein said mast is formed of a plurality of closed hollow members having ends that are connected at the top and the bottom of the mast.
- 12. (currently amended) A sailing boat according to claim 11, wherein said a tabernacle connects said ends of said closed hollow members at the bottom of the mast.
- 13. (previously presented) A sailing boat according to claim 9, wherein said hollow

member is at least partially filled with foam or other buoyancy-assisting material.

- 14. (currently amended) A sailing boat according to claim [[1]] 41, wherein said mast is mounted so as to afford tabernacle affords movement of the mast between an operative position in which it extends abeam of the hull and a stowed position in which it extends more fore and aft of the hull.
- 15. (original) A sailing boat according to claim 14, wherein the mast when in said stowed position extends substantially fore and aft of the hull.
- 16. (currently amended) A sailing boat according to claim 14, wherein said movement comprises tabernacle affords pivoting movement of the mast between said operative position and said stowed position.
- 17. (currently amended) A sailing boat according to claim [[1]] 41, wherein said main spar is connected to the mast at or adjacent a top centre point of the mast.
- 18. (currently amended) A sailing boat according to claim[[1]] 41, including stays for supporting opposite sides of the mast.
- 19. (original) A sailing boat according to claim 18, including stay adjustment means for adjusting said stays and thereby the take of the mast.
- 20. (currently amended) A sailing boat according to claim [[1]] 41, wherein said main spar extends at an angle in the range 35 to 55 degrees to the horizontal.
- 21. (original) A sailing boat according to claim 20, wherein said main spar extends at an angle in the range 40 to 50 degrees to the horizontal.
- 22. (original) A sailing boat according to claim 21, wherein said main spar extends at an angle of substantially 45 degrees to the horizontal.
- 23. (currently amended) A sailing boat according to claim [[1]] 41, wherein said hull is provided with a bowsprit and a forward end of said main spar is located on said bowsprit, forward of the bow of the hull.
- 24. (original) A sailing boat according to claim 23, including means for adjusting the position of said forward end of said main spar on said bowsprit.

- 25. (currently amended) A sailing boat according to claim [[1]] 41, wherein said main spar has a cross-section that tapers towards its upper end.
- 26. (currently amended) A sailing boat according to claim [[1]] 41, wherein said main spar has a degree of flexibility that increases towards its upper end.
- 27. (currently amended) A sailing boat according to claim [[1]] 41, wherein said mast is located at a distance from the bow of the hull that is in the range 25 to 40 percent of the length of the hull.
- 28. (original) A sailing boat according to claim 27, wherein said mast is located at a distance from the bow of the hull that is substantially one-third of the length of the hull.
- 29. (currently amended) A sailing boat according to claim [[1]] 41, wherein said sail has a lower, aft corner that is tethered substantially above the centre line of the hull.
- 30. (original) A sailing boat according to claim 29, including means for adjusting the position of said aft corner up to 100mm either side of the centre line of the hull.
- 31. (currently amended) A sailing boat according to claim [[1]] 41, wherein said sail extends from a position forward of the bow of the hull to a position substantially above the stern of the hull.
- 32. (currently amended) A sailing boat according to claim [[1]] 41, wherein said sail is of substantially triangular shape.
- 33. (currently amended) A sailing boat according to claim [[1]] <u>41</u>, wherein the dimensions and locations of said mast, main spar and sail are such that, when deployed, the sail cannot touch the mast.
- 34. (cancelled)
- 35. (currently amended) A sailing boat according to claim 41 34, wherein each said side portion of the mast extends outwardly of the hull for a distance equal to at least 20 per cent of the extreme beam of the hull.
- 36. (currently amended) A sailing boat according to claim <u>41</u> 34, wherein each said side portion of the mast extends outwardly of the hull for a distance equal to at least 30

per cent of the extreme beam of the hull.

- 37. (currently amended) A sailing boat according to claim <u>41</u> 34, wherein each said side portion of the mast extends outwardly of the hull for a distance equal to at least 40 per cent of the extreme beam of the hull.
- 38. (currently amended) A sailing boat according to claim <u>41</u> 34, wherein each said side portion of the mast extends outwardly of the hull for a distance equal to at least 50 per cent of the extreme beam of the hull.
- 39. (currently amended) A sailing boat according to claim <u>41</u> 34, wherein each said side portion of the mast extends outwardly of the hull for a distance equal to at least 60 per cent of the extreme beam of the hull.
- 40. (cancelled).
- 41. (currently amended) A sailing boat comprising:

a hull;

a mast that <u>is mounted directly or indirectly on the hull</u>, extends upwardly from one side of the hull and returns to a point substantially above the centre line of the hull; a main spar supported on the mast with the main spar extending upwardly from a lower, fore position forward of the mast to a higher, aft position aft of the mast; and a sail depending from the main spar for deployment to one side of the mast: wherein said mast extends outwardly from said hull prior to returning to said point.

42 - 44. (cancelled)